

IN THE CLAIMS:

1-9 (Canceled)

10. (Original) A wire-collecting device of a computer accessory, comprising:

a casing having a first opening and a collecting portion inside said casing for containing a signal-transmission device extending from said computer accessory;

a fastening device positioned on a first interior surface of said casing, and said fastening device being positioned near said first opening to clasp said signal-transmission device; and

an elastic element having a first terminal and a second terminal, said first terminal of said elastic element being installed into a second interior surface of said casing, and said second terminal of said elastic element being connected to said signal-transmission device to force said signal-transmission device to draw back into said collecting portion.

11. (Currently Amended) The wire-collecting device of claim 10, wherein said casing further comprises ~~a cover out of~~ cover that opens out from said first opening.

12. (Original) The wire-collecting device of claim 10, wherein said signal-transmission device includes a cable and a connector.

13. (Currently Amended) The wire-collecting device of claim 12, wherein said fastening device further comprises a second opening to enable said cable to pass ~~through~~ therethrough, said second opening is being wider than a diameter of said cable, and smaller than a width of said connector.

14. (Currently Amended) The wire-collecting device of claim 13, wherein said ~~mechanism~~ fastening device further comprises a recess for fastening said connector.

15. (Original) The wire-collecting device of claim 10, wherein said computer accessory is an external computer accessory.

16. (Currently Amended) The wire collecting device of claim 12 wherein ~~provided for a computer accessory, said wire securing device comprising:~~

~~a casing having a first opening and a collecting portion inside said casing for storing a cable of a the signal transmission device of said computer accessory; and~~

~~a fastening device positioned on a first interior surface of said casing, and near said first opening, said fastening device has~~ having a second opening and a recess, said second opening enabling said cable to pass ~~through~~ therethrough, and said recess being provided to fix said signal-transmission device,

wherein said signal-transmission device is drawn out of said recess, and pulled upwardly out of said fastening device by passing through said second opening when said computer accessory is used by a user, and said signal-transmission device is moved back into the fastening device and said signal-transmission device is clamped into said second opening after adjusting a an optimum length of said signal-transmission device.

17. (Currently Amended) The fastening wire collecting device of claim 16, wherein ~~said signal-transmission device includes a connector and a cable, and said second opening is wider than a diameter of said cable, and smaller than a width of said connector.~~

18. (Currently Amended) The fastening wire collecting device of claim 17, wherein ~~said cable is a helix cable.~~

19. (Currently Amended) The fastening wire collecting device of claim 18, wherein ~~the width of said second opening is smaller than a diameter of said helix cable.~~

20. (Currently Amended) The fastening wire collecting device of claim 16, wherein ~~said casing further comprises a cover that opens out of from said first opening.~~